







This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
D		MADE DRAWING FROM ORIGINAL DRAWING AT REV D. DELETED .05 AND .82 DIMENSIONS AS PER G.E.	5/31/2012	RJC	GE
5	16-0108	UPDATED TO NEW STANDARD. CH'D MAT'L WAS WHITE DELRIN IS WHITE DELRIN/ACETAL. CH'D ENGRAVE NOTE WAS ENGRAVE S/N, "MADE IN USA" IS LASER ENGRAVE S/N, "MADE IN USA" FILL WITH BLACK PAINT. ADDED ENGRAVE P/N FILL WITH BLACK PAINT NOTE.	8/11/2016	DEW	JAG



PART NO	A	B	C
269T9204	.805 .795	1.505 1.495	.155 .145
269T9204-3	.782 .772	1.515 1.505	.132 .122
269T9204-5	.875	1.642	.104

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	TOOL	WHITE DELRIN/ACETAL	1.00 X 1-3/4 X 5.00	1

DART AEROSPACE			
TITLE RIGGING TOOL-TAIL ROTOR LOW TIP SPEED			
DWG NO. 269T9204			REV 5
MAT'L WHITE DELRIN/ACETAL		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
HEAT TREAT		.XXX ± .005 FRACTIONS ± 1/8	
FINISH		.XX ± .01 ANGLES ± 5°	
SPEC		.X ± .1 SURFACES = 125/	
DRAWN BY: GILBERT		1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	
CHECKED: DUERFELDT		2. DIMENSIONAL LIMITS APPLY AFTER PLATING	
OPPS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
QA APPR: LINDSAY		USED ON MODEL	
APPROVED: GILBERT		269D	
SCALE 1:2	DATE 9/9/2011	SHEET 1 OF 1	